

POLYSTAR PREMIUM F/R™

TECHNICAL DATA SHEET

07th August 2019

WIDTH	250cm all colours / 300cm White only
ROLL LENGTH	30m
NOMINAL WEIGHT	720gsm
BASE FABRIC	Polyester 1222 Decitex
WEAVE	8 x 8 per/cm
COATING	PVC paste coated
SURFACE FINISH	High Gloss ROWACRYL protective finish
TEAR STRENGTH <small>WARP/WEFT</small>	490 / 430 N
TENSILE STRENGTH <small>WARP/WEFT</small>	3500 / 3100 N/5cm
ADHESION	110 N/5cm
U/V WARRANTY	3 year minimum
FIRE RETARDANT	AS/NZS 1530.2
TEMPERATURE RANGE	-30° / +70° C
ELONGATION AT BREAK <small>WARP/WEFT</small>	20% / 27%
FABRICATION METHODS	Hot Wedge, Hot Air or High Frequency Welding : Sewing : Adhesive
FABRIC CARE	OFPANZ Care Label OF-1

POLYSTAR

PREMIUM F/R PVC


COLOUR CHART



LIGHT BLUE



ROYAL BLUE




KELLY GREEN



EMERALD GREEN



DARK GREEN



LEMON YELLOW



YELLOW



ORANGE



CANDY RED




RED




LIGHT GREY



DARK GREY



WHITE



BLACK



BEIGE

Disclaimer:

Please note colours are computer generated and may not be an exact representation