



SUPERIOR HOLDING POWER,  
LIGHTWEIGHT, DURABLE & REUSABLE.  
INCREASE YOUR PRODUCTIVITY

---

## Baytex Earth Anchors

Increase your productivity with the screw in, screw out reusable earth anchors. Lightweight aircraft-quality cast aluminium 356 alloy.

SIMPLICITY · PERFORMANCE · STYLE




**Earth Anchor Load Capacity Pull Out Resistance**

| SOIL CLASS                   | PE9 PE9T<br>23cm<br>(9")     |                     | PE10<br>25cm<br>(10") | PE14-STD<br>37cm<br>(14") |                      | PE18<br>PE18-33<br>PE18SQ<br>46cm<br>(18") | PE26<br>66cm<br>(26") | PE36<br>91cm<br>(36") | PE46 Hex<br>PE46 Guy<br>1.2m<br>(46") |  |
|------------------------------|------------------------------|---------------------|-----------------------|---------------------------|----------------------|--------------------------------------------|-----------------------|-----------------------|---------------------------------------|--|
|                              | hardpan/ashphalt/clay        | 1.78 kN<br>(181 kg) |                       | 4.45 kN<br>(454 kg)       | 11.1 kN<br>(1311 kg) |                                            | 20.0 kN<br>(2039 kg)  | 37.4 kN<br>(3814 kg)  | 62.3 kN<br>(6351 kg)                  |  |
| 1 Cohesive soil              | 0.89 kN<br>(91 kg)           |                     | 3.11 kN<br>(317 kg)   | 7.56 kN<br>(771 kg)       |                      | 13.8 kN<br>(1407 kg)                       | 26.9 kN<br>(2743 kg)  | 42.3 kN<br>(4312 kg)  |                                       |  |
| 2 Medium density soil        | 0.44 kN<br>(45 kg)           |                     | 1.56 kN<br>(159 kg)   | 2.67 kN<br>(272 kg)       |                      | 4.89 kN<br>(498 kg)                        | 9.34 kN<br>(952 kg)   | 14.7 kN<br>(1498 kg)  |                                       |  |
| 3 Loose med-to-fine sand     | 0.44 kN<br>less than (45 kg) |                     | 0.89 kN<br>(91 kg)    | 1.56 kN<br>(159 kg)       |                      | 2.80 kN<br>(285 kg)                        | 4.45 kN<br>(453 kg)   | 8.90 kN<br>(907 kg)   |                                       |  |
| 4 Loose fine uncompactd sand | 0.44 kN<br>less than (45 kg) |                     | 0.44 kN<br>(45 kg)    | 0.89 kN<br>(91 kg)        |                      | 1.60 kN<br>(163 kg)                        | 1.56 kN<br>(159 kg)   | 4.89 kN<br>(498 kg)   |                                       |  |

**PE9**


20mm hex head  
32mm flange  
16mm neck diameter  
29mm flight diameter



23cm


**PE9T**

10cm handle  
13mm neck diameter  
29mm flight diameter



**PE10**

26mm hex head  
5cm flange  
26mm neck diameter  
45mm flight diameter




25cm

0.5kg

**PE14-STD**

15cm steel stud with washer & nut  
5cm flange  
36mm neck diameter  
58mm flight diameter




37cm  
30cm

Tapped hole: 1/2" 113 thread 64mm depth  
1/2" square drive

0.85kg

**PE18SQ**

1/2" square drive  
5cm flange  
26mm neck diameter  
45mm flight diameter




46cm

.6kg

**PE18**

26mm hex head  
5cm flange  
26mm neck diameter  
45mm flight diameter




46cm

0.7kg

**PE26**

26mm hex head  
5cm flange  
26mm neck diameter  
45mm flight diameter




66cm

0.7kg

**PE36 Hex**

51mm hex head  
10cm flange  
45mm neck diameter  
77mm flight diameter




90cm

4.0kg

**PE46 Hex**

51mm hex head  
10cm flange  
45mm neck diameter  
77mm flight diameter




1.2m

4.8kg

**PE46 Guy**


51mm hex head  
45mm neck diameter  
77mm flight diameter



4.6kg

**PE18-33**

26mm hex head  
5cm flange  
26mm neck diameter  
33mm flight diameter




46cm

0.7kg

Base Plate: 7mm plate = 30mm hole

Tapped for 3/8" bolt



9.5mm clear hole for sleeve bolt or grounding wire

**New Zealand**  
52 Newton Street,  
PO Box 4370, Mount Maunganui  
New Zealand

tel +64 7 579 0190  
www.baytex.co.nz  
info@baytex.co.nz

**Australia**  
tel 1800 766 661  
www.baytex.com.au  
info@baytex.com.au



PE9-PE26

Milwaukee Cordless Impact Wrench M18  
1/2" Drive 950 NM Torque (M18CHI-  
WF12-502C)



1" 6-Sided Long-reach  
Impact Socket 1/2" Drive



Ship Auger: soil auger  
18mm x 460mm



7/16" to 1/2" Hex to  
Ships Auger Coupling

PE36-PE46

Makita Electric Impact Wrench  
1" Drive (MAK-TW1000)



2" 6 pointed LR  
Impact Socket 1" Drive



Earth Auger 2"x 36"  
with 1" Sq Drive  
Adaptor



# RECOMMENDED TOOLS

## Baytex Earth Anchors